SECTION 10500 PISTOL LOCKERS

PART 1 – GENERAL

1.01 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 1 specifications apply to this section.

1.02 SUMMARY

- **A.** This Section includes the following:
 - 1. FLC-707-4 (table mount) & FLC-707-4W (Wall mount) Light Duty Law Enforcement Pistol Lockers, including the following:
 - a. 1 &,4, compartment standard sizes
 - b. Custom sizes also available
 - 2. Provide fasteners and anchorage devises to install lockers provided under this section.

1.03 SUBMITTALS

- **A.** Product Data: Include construction details, material descriptions, dimensions of individual components and profiles, and finishes for each type of locker.
- **B.** Shop Drawings: Provide drawings as necessary to detail the plan, section and elevation of each unit. Coordinate sizes, models and locations with the contract documents
- C. Provide drawings detailing the layout of each unit or bank of lockers.
- **D.** Samples for verification: Adherence to the specification is required. Locker submitted must meet specification regardless of manufacturer's standard product. Submit manufacturer's technical data and installation instructions for metal locker units.

1.04 QUALITY ASSURANCE

- **A.** Uniformity: All primary products specified in this section will be supplied be a single manufacturer with a minimum of 10 years experience
- **B.** Installers Qualifications: Lockers to be installed by an experienced agent of the Manufacturer with a minimum of 5 years experience in installing products of a similar type.

1.05 DELIVERY, STORAGE, AND HANDLING

A. Packing and Shipping: Do not deliver metal lockers until building is enclosed and ready for locker installation.

B. Storage and Protection: Store products in manufacturers original packing until ready to install

1.06 WARRANTY

A. Locker manufacturer shall warrant the lockers for five years use of the original purchaser from date of shipment. Warranty shall include all defects in material and workmanship, excluding finish, vandalism and improper installation.

PART 2 – PRODUCTS

2.01 MANUFACTURERS

- **A.** Acceptable Manufacturers: Subject to compliance with requirements of the Contract Documents, acceptable manufacturers are as follows:
 - **1.** Fasco Inc

2.02 FABRICATION

A. Locker Construction

- **1.** Lockers to be all welded construction with exposed welds sanded smooth.
- 2. No bolts, screws or rivets used in assembly of locker body.
- **3.** Ship lockers fully assembled, ready to be installed in place in accordance with manufacturer's instructions.

B. Body of Lockers:

- 1. Body shall be constructed of 1 continuous piece of 16 ga cold rolled or hot rolled pickled & oiled steel sheet
- 2. Back: Solid sheet of 16 gauge cold rolled sheet steel welded to frames of sides
- **3.** Internal framing & door stops shall consist of 16 ga steel frame, cut out to form a continuous frame around each compartment door.

C. Doors:

- **1.** Doors are 16 ga steel, cut out to fit so the face is flush with the front of the cabinet to resist prying.
- 2. Furnish a 16 ga steel compartment body welded to the back side of each door to securely hold the firearm
- **3.** Line each compartment body with 1/8" thick out door felt lining

E. Locks

1. Each compartment shall be locked with a grooved key cam lock, individually keyed & master keyed

F.Hinges:

1. 16 gauge continuous piano hinge welded to the door & riveted to the frame,

G. Finish:

- **1.** Complete locker unit to be thoroughly cleaned, phosphatized and sealed.
- 1. Finish to be baked on polyester powder coat
- 2. Color of lockers shall be light tan in color

2.03 LOCKER ACCESSORIES

A.

PART 3 – EXECUTION

3.01 INSTALLATION

- **A.** Wall Installation:
 - **1.** Securely anchor every locker to wall or counter before use.
 - 2. Anchoring to be determined by conditions at time of installation.

3.02 ADJUSTING

METAL LOCKERS 10500

A. General Requirements: Upon completion of installation, inspect lockers and adjust for proper door and locking mechanism operation.

3.03 CLEANING

A. General Requirements:

- **1.** Clean interior and exposed exterior surfaces, removing debris, dust, dirt, and foreign substances on exposed surfaces.
- 2. Touch up scratches and abrasions to match original finish.
- **3.** Polish stainless steel and non-ferrous metal surfaces.
- 4. Replace locker units that cannot be restored to factory-finished appearance.
- 5. Use only materials and procedures recommended or furnished by locker manufacturer.